



# STEP BY STEP DEPLOYMENT INSTRUCTIONS

Thank you for your recent purchase of one of the most unique and carefully crafted covers. It is designed for those who want to protect their items from rodents, weather, heat and sun damage. Here are some helpful tips on using your new cover.



**1.** Place bag on the side of your vehicle (car or short bed truck). Unroll the cover with the weighted apron closest to your car. Note: The cover is marked "Front" for the front of the vehicle and the back of the cover has the CoverSeal logo.

**2.** Starting on the side the cover is unrolled, begin deployment at the front for vehicle and back for truck, raise the edge so that the silver side is on the outside and the white side is facing your vehicle.

**3.** Begin lifting the cover onto your vehicle hood or into truck bed.

**4.** Utilizing the side mirrors, turned inward, work your way down the vehicle lifting the cover up on the roof pulling cover half-way over the vehicle by the time you reach the opposite end. Note: If you have a fin or roof rack bars, lift over to help hold cover in place.

**5.** Finish deployment by going back to where you started, on the opposite side, pulling the cover down, working your way to the opposite end. Utilize the weighted bottom to help drop the cover to the ground.

**6.** Once cover is on your vehicle, center the front and back logo. Walk around your vehicle 360 degrees to confirm the weighted apron is resting on the ground evenly.

**Weather protection:** CoverSeal material is durable and breathable. It reflects 90% of the sun's damaging rays. The covers are made intentionally loose. The loose fit keeps precipitation from puddling on the cover leading to mold.

**Use and cleaning your cover:** Dirt from loose gravel driveways/carports can simply be wiped-off your cover with a towel before and after deployment.

**Fixing a damaged cover:** In the slight chance your cover gets caught on a sharp edge and a small tear occurs, it's important to stop any rip quickly. In the event this happens, we have found using silver (for the cover) or black (for the apron) heavy duty tape can extend the life of the cover by stopping the rip. Use a strip of heavy duty tape roughly 1/2 inch longer than the tear on the inside and another on the outside of the cover to create a patch. Forming a double-sided patch will eliminate adhesive from touching your vehicle.

**CAUTION:** 

ONLY use for covering outdoor patio furniture or grill. Remove cover completely before turning appliance "on" or putting in start mode. Turn "off" before recovering

[www.getcoverseal.com](http://www.getcoverseal.com) | [support@getcoverseal.com](mailto:support@getcoverseal.com)

CALL US! 669.208.2601